



K 5600[®]

L I G H T I N G

K 5600, INC. 10434 Burbank Blvd. North Hollywood, CA 91601 • Tel: (818) 762.5756 • (800) 662-5756 • Fax: (818) 762.6629 • www.K5600.com

Products That Define The Word:



ver-sa-tile \vər-sət-ī-əl *adj* : turning with ease from one thing or position to another.

BUG ADVANTAGE

JOKER NEWS 400

INFORMATION:

The Joker News 400 system was designed specifically for the fast pace and quick set ups of news coverage. The ultra fast re-strike lamp starter assures quiet and immediate lamp ignition and re-ignition. This innovative fixture has retained the qualities of the Joker-Bug system, offering two fixtures in one: an Omni-directional fixture and a directional focus-able open face Flood.

The Joker News 400 requires virtually no set up time, the focusing of the parabolic reflector changes the beam pattern from Spot to Flood in a 3 to 1 ratio, achieving beam angles from 16 to 45 degrees. Used without optics (News Beamer detached) the Joker News becomes a Bug-Lite. This very open source is ideal to fill evenly a Lightbank or a Lantern making it the perfect light for interviews. Its lightweight allows it to hang safely at the end of a boom arm. The Joker News 400 will travel and operate in 110 and 220 Volt environments as well as 24/30 Volt belts and packs with our Slimverter 400.



JN400 Kit



Size: 11.5" x 16.5" x 17"



JN400 in Lightbank



JN400 in Lantern

VERSATILE.



K 5600[®]

L I G H T I N G

K 5600, INC. 10434 Burbank Blvd. North Hollywood, CA 91601 • Tel: (818) 762.5756 • (800) 662-5756 • Fax: (818) 762.6629 • www.K5600.com

VERSATILE.

Products That Define The Word:



ver·sa·tile \vər-sət-əl *adj* : turning with ease from one thing or position to another.

BUG ADVANTAGE



JN400 with Clear and Frosted Beaker



DC Operations

JOKER NEWS 400

SPECIFICATIONS:

- Lamp Housing: Aluminum casting, high temperature black epoxy, striker compartment is light gray epoxy.
- Safety Glass Beaker: Borosilicate UV filter tempered.
- Yoke: 5/8" Baby size receptacle, Aluminum casting black epoxy finish. Large brake area for use of front end lightbanks, speed rings, louvers and lanterns.
- Lamp: MSR 400 HR, 5600 Kelvin, 400 hours life.
- Power Supply: Electronic, square wave flicker free. AC input: 90-132 V or by sliding selector switch: 180-265 V. 50 or 60 Hz. Dual function ON-OFF push button switch. Completely silent (convection cooled)
- Connectors: Veam quarter turn quick locking.
- Extension cable: 25', 8 feet attached to the head.
- NEWS BEAMER: Solid one piece machined aluminum with replaceable ears.
- Clear anodized. Focusing by very short radial action. Integrated design.
- Reflector: 4 3/4" diameter stippled parabolic electrolytically coated.
- Accessory size: 6 5/8"
- Accessories: Barndoor, Dicroic, Scrims.

Photometrics:

dis.	Spot fc.	Diam. ft.	Flood fc.	Diam. ft.
3'	8400	0.8	2800	2.5
6'	2100	1.7	700	5

